

**YCL60** SERIES



**Input: 100-240VAC 50/60Hz**

**Output Voltage: 5V-24V DC**

**Rated Power: 60W max**

**Features**


- Universal Input: 200-240V AC 50/60Hz
- RoHS Compliance
- EMI Standard EN55015:2019+A11
- Safety Standard: EN61347-1:2015, EN61347-2-13:2014+A1:2017, UL8750
- Inrush current < 65A AC230V/50Hz
- High efficiency & low power consumption
- Short Circuit, Over Current and Over Voltage Protection
- Over temperature protection
- 100% full load burn-in test
- Dimming available

**Application**

- LED lights bring
- LED indoor lighting
- LED decorative lighting
- LED building lighting



■ **Dimensions and Installation**




**YCL60** SERIES

MODEL DETAIL SPEC.		YCL60-1205000	YCL60-2402500
INPUT	Input Voltage:	100-240VAC/ 200-240VAC	
	Input Frequency:	50/60Hz	
	Inrush Current:	65A/230VAC at full load	
	AC Current:	0.21A/230VAC	
	Leakage Current:	< 0.25mA/240VAC	
	Efficiency:	87%	87%
OUTPUT	DC Voltage:	12V	24V
	Rated Current:	5000mA	2500mA
	Rated Power:	60W	60W
	Voltage Tolerance:	±5.0%	±5.0%
	Ripple and Noise:	120mVp-p	240mVp-p
	Line Regulation:	±3%	
	Load Regulation:	±5%	
	Setup, Rise, Hold Up time:	1s, 10ms/60ms 230VAC 1000ms, 1ms/25ms 115VAC at full load	
ENVIRONMENTAL	Operating Temperature:	-20 ~ +60 (Refer to "Derating Curve")	
	Storage Temp:	-40°C ~ 85°C	
	Storage Humidity:	20 ~ 95% RH	
	Working Humidity:	20 ~ 95% RH non-condensing	
PROTECTION	Over Load:	Above 105% rated output power	
		Protection type: Hiccup mode, recovers automatically after fault condition is removed	
	Over Voltage:	12V:13.8 ~ 16.2V 24V:27.6 ~ 32.4V	
		Protection type: Shut down o/p voltage, re-power on to recover	
Over Temperature:	Shut down o/p voltage, re-power on to recover		
SAFETY & EMC	Safety Regulations:	EN61347-2-13:2014+A1:2017,EN61347-1:2015;EN62493:2015	
	Withstand Voltage:	I/P-O/P:3750KVAC	
	Harmonic	EN61000-3-2 Class C EN61000-3-3	
	EMI:	Compliance to EN55015	
	EMS :	Compliance to 61547:2009	
OTHER	MTBF:	200,000 Hours Minimum at Full Load at 25°C Ambient	
	Size:	163*43*33mm	
	Weight:	380g / pcs	
	Packaging:	50PCS/CTN	


**YCL60** SERIES

**Deduction curve  
and temperature**



Environment temperature(°C)

**Minus output  
and input voltage curves**



Input voltage(VAC)

**Functional Diagram**

