








LED Drivers





Universal Science selected list






Slim Constant Voltage 24V/48V IP20

	Code	L x W x H	Input	Output current	Output power	Output voltage
	DYSL30TV24	251x30x16mm	220-240VAC	—	30W	24V
	DYSL60TV24UL	320x30x19mm	100-240VAC	—	60W	24V
	DYSL100TV24	320x30x19mm	220-240VAC	—	100W	24V
	DYSL200TV24	360x32x24mm	220-240VAC	—	200W	24V
	DSLTI0024VFGSE	298x29.8x16.5mm	110-240VAC	—	100W	24V
	DSLTI0048VFGSE	298x29.8x16.5mm	110-240VAC	—	100W	48V





Standard Constant Voltage 24V IP20

	Code	L x W x H	Input	Output current	Output power	Output voltage
	DYSL15V24	90x40x24mm	220-240VAC	—	15W	24V
	DSLTI3024VLGESE	165x40x30mm	220-240VAC	—	30W	24V
	DSLTI6024VLGESE	188x45x30mm	220-240VAC	—	60W	24V
	DSLTI5024VLG-E	185x60x31mm	220-240VAC	—	150W	24V

Standard Constant Voltage 12V/24V IP67

	Code	L x W x H	Input	Output current	Output power	Output voltage
	DYCL060V24	163x43x33mm	220-240VAC	—	60W	24V
	DYCL100V12	190x52x37mm	200-240VAC	—	100W	12V
	DYCL100V24	190x52x37mm	200-240VAC	—	100W	24V
	DYCL150V12	191x52x37mm	220-240VAC	—	150W	12V
	DYCL150V24	191x52x37mm	220-240VAC	—	150W	24V





Constant Current Dip-Switch e DALI2

	Code	L x W x H	Input	Output current	Output power	Output voltage
	DSL20500IBUSE	66.7x41x22mm	110-277VAC	150-500mA	20W	5-40V
	DSL20KITBTOIN	End cap kit for independent application				
	DSL25600ILSE	85.3x41x22mm	220-240VAC	250-600mA	25W	27-42V
	DSL20500ILDU	103x41x22mm	110-277VAC	150-500mA	20W	8-40V
	DSL2351000ILDU	139x42x30mm	110-277VAC	250-1000mA	35W	8-42V




DIP SWITCH

DALI2



High Performance IP67 DALI2



	Code	L x W x H	Input	Output current	Output power	Output voltage
	DBLD150V024ANS	161x67.5x33.5mm	90-305VAC	—	150W	24V
	DLC0240V024ANS	162x68x38.5mm	108-305VAC	—	240W	24V
	DCP0320V024ANS	225x68x38.5mm	90-305VAC	—	320W	24V
	DBLD400V024ANS	240x90x41.5mm	90-305VAC	—	400W	24V

High Performance IP67 Dimming 1-10V

	Code	L x W x H	Input	Output current	Output power	Output voltage
	DBLD150V024DNS	161x67.5x33.5mm	90-305VAC	—	150W	24V
	DLC0240V024DNS	162x68x38.5mm	108-305VAC	—	240W	24V
	DCP0320V024DNS	225x68x38.5mm	90-305VAC	—	320W	24V
	DBLD400V024DNS	240x90x41.5mm	90-305VAC	—	400W	24V

Industrial


	Code	L x W x H	Input	Output current	Output power	Output voltage
	DYSI036V24	110x78x36mm	100-265VAC	—	36W	24V
	DYSI080V24	130x98x42mm	100-265VAC	—	80W	24V

	Code	L x W x H	Input	Output current	Output power	Output voltage
	DYSI100V24	160x98x42mm	100-265VAC	—	100W	24V
	DYSI150V24	160x98x42mm	100-265VAC	—	150W	24V



Din Rail

	Code	L x W x H	Input	Output current	Output power	Output voltage
	DYSDL60V24	100x90x40mm	90-264VAC	—	60W	24V
	DYSD100SV24	70x90x58mm	90-264VAC	—	92W	24V
	DYSDN150V24	165x30x25mm	90-264VAC	—	150W	24V
	DYSDN240V24	125.2x113.5x63mm	100-264VAC	—	240W	24V
	DYSDB2024V	125.x110x63mm	24Vdc (BUFFER)	20A	480W	24V

Zhaga Socket/Nema Socket

	Code	Size	Pins	Rated current	Op.Temperature	IP grade
	CNEMA7P	Ø66mm x 31mm	7	10 A	-40°C to 80°C	IP66

Zhaga Socket/Nema Socket

	Code	Size	Pins	Rated current	Op.Temperature	IP grade
	CNEMACAPS	Ø73.2mm x 39mm	—	10 A	-40°C to 80°C	IP66
	CZHAGA4P	Book 18 compliant	4	1.5 A	-40°C to 80°C	IP66

Partners



Universal Science srl - Società con unico socio
 Via adige, 30 - 20006 Pregnana Milanese (MI) - Italy
 Tel: +39 02 94324 511 - Email: sales@universal-science.it